

The NEW Rigging Rope Wrench applies friction to a lowering line whilst anchored at the top of the tree. This means that not only is the device controllable from the ground, but the line can also be passed to the climber in the treetop, should they need to take control.

Giving control to the climber is useful when working in smaller crews, or when the grounds-person is struggling to control the lowered section and the end of the line at the same time. With the Rigging Rope Wrench the climber can control the rope, leaving the grounds-person's hands free to control the lowered section. In the event of needing to lift a section over an obstacle, or apply upwards tension, the Wrench element will disengage, removing the applied friction and allow a smooth haul up.



The Rigging Rope Wrench has been optimised for 13mm (1/2") rope, making it the ultimate lightweight rigging kit, when teamed with hollow-braid slings.

For added versatility, the Rigging Rope Wrench can be placed in the traditional position at the base of the tree. In this position, additional pulleys can be rigged, in order to increase mechanical advantage, for ease of lifting heavy loads.

Options

RP290 Bushed

Suitable for light loads (of up to 70kg/154lbs).

RP292One-way Locking Bearing

For loads ranging from 20 to 120kg (44-264lbs).

One-way locking wheel, provides additional friction when lowering, allowing increased control of heavy loads, during lowering. During lifting, the wheel runs freely.



Disengaged (During Lifting)



(During Loadarrest/lowering)

For further information, please contact us:

+44 (0) 1248 363 110

sales@iscwales.com www.iscwales.com climb. work. rescue.