

WG-640 Lite Cut 3



PROTECTION

- Cut-resistance

NORMS



EN388:
2016



4342C



CUT

DOCUMENTS

You can also download on our website :

- Product technical sheet
- EU certificate
- Declaration of Conformity
- Food contact information
- User instructions

APPLICATIONS

- Installation and handling of sharp parts or objects
- Automotive
- Metallurgy
- Steel industry
- Recycling
- Industrial maintenance
- Sorting
- Assemblage
- Assembly

INFORMATION

Coating

Nitrile single dip, Palm fit

Liner

Nylon and Technical Fiber, Grey / Black

Gauge

13

Packaging

12 pairs / polybag

144 pairs / box

DIMENSIONS

Tolerance $\pm 5\%$

SIZE	6 / XS	7 / S	8 / M	9 / L	10 / XL	11 / XXL
Hem Color	Red	Purple	Black	Grey	Yellow	Beige
Overall Length (mm)	220	232	244	257	260	272
Palm width (mm)	84	90	94	99	103	110
Length of middle finger (mm)	68	73	75	80	80	88
Thickness (µm)	1320	1310	1330	1320	1350	1360
Weight (g/paire)	47.79	57.58	60.99	67.14	71.34	78.59
Liner Weight (g/pair)	35.54	44	45.43	49.62	52.02	56.9
Coating Weight (g/pair)	12.3	13.6	15.6	17.5	19.3	22.1

CARTON INFORMATION

Carton Volume (m,m³)	Length 0.530 x Width 0.315 x Height 0.280 : Volume 0.047 (m³)					
Carton Net Weight (kg)	6	6.5	7.0	7.5	8.9	9.5
Carton Gross Weight (kg)	7	7.5	8.0	8.5	9.9	10.5